

This data sheet covers both the self adhesive and sew on hook & loop products sold on [www.tradeshopdirect.co.uk](http://www.tradeshopdirect.co.uk)

<b>Tape Durability</b>		
<i>Peeling Cycle</i>	<i>Closure Strength Reducing Rate</i>	<i>Changes to Loop Tape</i>
2000 times	Under 15%	No Fluffing
5000 times	Under 25%	Little Fluffing
10000 times	Under 35 %	Obvious Fluffing
20000 times	Under 50%	Fluffing Throughout

<b>Tape Colour Fastness</b>		
<i>Test Item</i>	<i>Test Method</i>	<i>Evaluation</i>
Against Washing	JS-L-0844-1976A-4	Class 3 or Superior
Against Hot Water	JS-L-0845-1975-3	Class 3 or Superior
Against Sweat	JS-L-0848-1974-A	Class 3 or Superior
Against Rubbing	JS-L-0849-1971	Class 3 or Superior

<b>Tape Strength</b>		
<i>Width (mm)</i>	<i>Shear Strength</i>	<i>Peel Strength</i>
16	Over 5.3kg	Over 130gM
20	Over 7.5kg	Over 180gM
25	Over 10.0kg	Over 250gM
30	Over 12.0kg	Over 290gM
38	Over 15.0kg	Over 360gM
50	Over 18.0kg	Over 440gM
100	Over 35.0kg	Over 840gM
Fastening length 50mm, under conditions of 20 degrees C & 65% Relative Humidity		